

Secomatic®

SMX Series Washer Extractor



Professional Create Value



30-130kg Automatic Industrial Washer Extractor

- Large door opening for easy loading and unloading.
- High-density flat hole technology of drum, perforated V-ribs for better cleaning result.
- Anti-corrosion, tub and all metal part connect with water are AISI 304 stainless steel ensure long lifespan.
- Heavy stainless steel material structure design, absorb vibration rate is up to 97%, freestanding.
- Five soap box, unique tilt stainless steel door for not leakage.
- High spin testing under large capacity of unbalanced loading ensure long lifespan of structure.
- Narrow water tank design, improve water utilization, reduce detergent consumption, energy save.
- 300 G-factor, standard double water inlet, save water and time.
- Unbalance design ensure balance of linen, efficient extraction.
- Comprehensive security control system, water pressure lever diagnostic, more reliable.
- High quality seal from German supplier, guaranty stable performance.
- Fully programmable microprocessor, USB port available.
- Optional : * Detergent connect system * Second drain system
 * Cambered loading part * Reuse water inlet

Technical Parameters

Model No	Unit	SMX-65S	SMX-110S	SMX-155S	SMX-220S	SMX-285S
Heat Source	Steam/Electric	Steam/Electric	Steam/Electric	Steam	Steam	Steam
Capacity	kg	30	50	70	100	130
Drum Diameter	mm	902	1069	1090	1240	1300
Drum Depth	mm	500	610	760	840	960
Inverter Power	kw	5.5	7.5	11	11	15
Motor Power	kw	4	5.5	7.5	7.5	11
Multilingual Microprocessor	30 Programmable programs +Maunal					
Washing Speed	rpm	37	36	35	32	32
Spin Speed	rpm	750	720	700	650	640
G-factor	G-factor	300	300	300	300	300
Stainless Steel AISI 304		Standard	Standard	Standard	Standard	Standard
Cage & Cage House AISI304		Standard	Standard	Standard	Standard	Standard
Electrical	V/Ph/Hz	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50
Steam Pressure	bar	4~6	4~6	4~6	4~6	4~6
Cold Water Inlet	inch	11/2	11/2	11/2	11/2	11/2
Hot Water Inlet	inch	11/2	11/2	11/2	11/2	11/2
Steam Inlet	inch	1	1	1	1	1
Recycling Drain(optional)	inch	/	11/2	/	11/2	/
Drain	mm	140	140	140	140	140
Compression Air Inlet	mm	φ8	φ8	φ8	φ8	φ8
Weight	kg	1600	2500	2800	3200	4300
Width	mm	1460	1700	1650	1810	1940
Depth	mm	1440	1730	1960	2010	2210
Height	mm	1870	2080	2108	2340	2195

- 1.Manufacturer reserve the right to change the installation information without notice.
- 2.Graphic size range of plus or minus 10mm.
- 3.Please read the connection information from chart and list.
- 4.Customised different area power supply.
- 5.For more informaton please contact with manufacturer.



深圳中施机械设备有限公司 深圳观澜美泰科技园1号厂房
Castic-SMP Machinery Corp Ltd Building1,Meitai Industry Zone,Guanlan Town,Shenzhen,China
 电话T:+86-755-26639452 / 传真F:+86-755-26632860 / 电邮E:info@castic-smp.com.cn

www.castic-smp.com