

## Dryers



## Performance

- Electrostatically painted panels and anti-corrosive stainless steel Cylinder and rear cover.
- Belt Drive with less noise, efficient& space saving.
- Large glass door.
- Advanced control system with multiple formulas.
- Schneider electric components and Crouzet micro switch to guarantee safer and reliable machine operation.
- Exquisite and durable belt pulley.
- Advanced humidity control system to bring energy-saving effect and maintain linen softness.

| 型号                         |        | 单位      | SE-3030      |        | SE-30   |   |       | SE-55   |    |        | SE-75   |    |        | SE-120    |    |        | SE-170    |        | SE-200      |        |
|----------------------------|--------|---------|--------------|--------|---------|---|-------|---------|----|--------|---------|----|--------|-----------|----|--------|-----------|--------|-------------|--------|
|                            |        |         | E            | G      | S       | E | G     | S       | E  | G      | S       | E  | G      | S         | E  | G      | S         | G      | S           | G      |
| Rated Load                 |        | Lb (kg) | 30×2(13.5×2) |        | 30(15)  |   |       | 55(25)  |    |        | 75(34)  |    |        | 120(54)   |    |        | 170(77)   |        | 200(86-100) |        |
| Basket<br>(diameter*depth) |        | mm      | 2×770×704    |        | 770×704 |   |       | 937×700 |    |        | 937×900 |    |        | 1130×1035 |    |        | 1290×1080 |        | 1290×1270   |        |
| Basket Volume              |        | L       | 2×313        |        | 313     |   |       | 482     |    |        | 620     |    |        | 1037      |    |        | 1411      |        | 1656        |        |
| Motor                      | Basket | kw      | 2×0.15       |        | 0.15    |   |       | 0.25    |    |        | 0.25    |    |        | 0.75      |    |        | 2.25      |        | 2.25        |        |
|                            | Blower |         | 2×0.18       |        | 0.18    |   |       | 0.25    |    |        | 0.25    |    |        | 0.55      |    |        | 1.13      |        | 1.13        |        |
| Electric Heated Power      |        | kw      | 16           | —      | —       | 8 | —     | —       | 16 | —      | —       | 24 | —      | —         | 48 | —      | —         | —      | —           | —      |
| Steam Consumption          |        | kg/h    | —            | —      | 25      | — | —     | 55      | —  | —      | 65      | —  | —      | 85        | —  | —      | 100       | —      | 120         | —      |
| Gas Consumption            |        | btu/h   | —            | 140000 | —       | — | 60000 | —       | —  | 100000 | —       | —  | 140000 | —         | —  | 200000 | —         | 280000 |             | 400000 |
| Steam Fittings             |        | mm      | —            | —      | 20/20   | — | —     | 20/20   | —  | —      | 20/20   | —  | —      | 25/25     | —  | —      | 25/25     | —      | 25/25       | —      |
| Gas Fittings               |        | mm      | —            | 20     | —       | — | 20    | —       | —  | 20     | —       | —  | 20     | —         | —  | 20     | —         | 20     | —           | 20     |
| Exhaust Diameter           |        | mm      | 190×300      |        | 190×300 |   |       | 202     |    |        | 202     |    |        | 250       |    |        | 300       |        | 300         |        |
| Air Flow                   |        | cmm     | 35           |        | 20      |   |       | 34      |    |        | 45      |    |        | 59        |    |        | 71        |        | 84          |        |
| Dimensions                 | Width  | mm      | 800          |        | 800     |   |       | 1020    |    |        | 1020    |    |        | 1270      |    |        | 1450      |        | 1550        |        |
|                            | Depth  | mm      | 1085         |        | 1070    |   |       | 1080    |    |        | 1080    |    |        | 1730      |    |        | 1730      |        | 2030        |        |
|                            | Height | mm      | 1937         |        | 1645    |   |       | 2030    |    |        | 2030    |    |        | 2280      |    |        | 2490      |        | 2490        |        |
| Weight                     |        | kg      | 280          |        | 180     |   |       | 300     |    |        | 330     |    |        | 700       |    |        | 900       |        | 1200        |        |

Specifications and appearance subject to change without notice.  
Contact factory for acoustics data.

## Vacuum Tables

### IB-A Vacuum Table

- Large vacuum table, low noised, with iron rest and swing away sleeve arm.
- Dimensions:1380x780x850mm.
- Weight:38kg.
- Power supply:380V/3Ph/50Hz.

### Optional Accessories

- A variety of additional sleeve shapes are available.



Model IB-A



深圳中施机械设备有限公司 深圳观澜美泰科技园1号厂房

Castic-SMP Machinery Corp Ltd Building 1, Meitai Industry Zone, Guanlan Town, Shenzhen, China

电话 T : +86-755-26639452 / 传真 F : +86-755-26632860 / 电邮 E : info@castic-smp.com.cn

[www.castic-smp.com](http://www.castic-smp.com)

2017.07